

Specifications

Frequencies		UHF1: 400-470MHz; UHF2: 450-520MHz UHF3: 350-400MHz; VHF: 136-174MHz
Channel Capacity		16
Channel Spacing		12.5KHz/20KHz/25KHz
Operating Voltage		13.6V ± 15%
Channel Capacity	Standby	<0.8A
	Transmit	<1.1A
Frequency Stability		± 0.5ppm
Antenna Impedance		50 Ω
Duty Cycle		100%
Dimensions (H x W x D)		88 X 483 X 366 mm
Weight		8.5Kg
LCD Display		220*176 pixels, 262000 colors; 2.0 inch, 4 rows
Sensitivity	Analog	0.3 μ V (12dB SINAD); 0.22 μ V (Typical) (12dB SINAD); 0.4 μ V (20dB SINAD)
	Digital	0.3uV/BER5%
Adjacent Channel Selectivity TIA-603 ETSI		65dB @ 12.5KHz ; 75dB @ 20/25KHz
Intermodulation TIA-603 ETSI		75dB @ 12.5/20/25KHz 70dB @ 12.5/20/25KHz
Spurious Response Rejection TIA-603 ETSI		80dB @ 12.5/20/25KHz 80dB @ 12.5/20/25KHz
Blocking TIA-603 ETSI		90dB 90dB
Hum and Noise		40dB@12.5KHz 43dB@20KHz 45dB@25KHz
Rated Audio Power Output		0.5W
Rated Audio Distortion		≤ 3%
Audio Response		+1 ~ -3dB
Conducted Spurious Emission		<-57dBm

RF Power Output	5-50W
FM Modulation	11K0F3E @ 12.5KHz; 14K0F3E @ 20KHz; 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD; 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz; -30dBm >1GHz
Modulation Limiting	± 2.5KHz @ 12.5KHz; ± 4.0KHz @ 20KHz; ± 5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz; 43dB @ 20KHz; 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz; 70dB @ 20/25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤ 3%
Digital Vocoder Type	AMBE++ or SELP
Digital Protocol	ETSI-TS102 361-1,-2,-3

Environmental Specifications	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C

All Specifications are tested according to applicable standards, and subject to change without notice due to continuous development.

Standard Accessories

Power Cord

Optional Accessories



Pictures above are for reference only and may vary from actual products.



RD98X

Powerful Digital Repeater

- Smart Digital-Analog Switch
- Outstanding Heat Dissipation





Product Features

- **Smart Digital-Analog Switch**
This repeater supports digital and analog modes. It can smartly select the right one based on the type of received signal, allowing you to enjoy digital delights with ease.
- **Advanced TDMA Technology**
The application of Time Division Multiple Access (TDMA) technology greatly enhances spectrum efficiency, which allows twice the user compared with that of traditional FDMA. Obviously, this can not only save your cost in base station and frequency license, but also relieve the pressure of increasing shortage in spectrum resources.
- **Outstanding Heat Dissipation**
The unique cooling design combining a built-in heat pipe and a temperature-controlled fan ensures quick heat dissipation, enabling the repeater to work normally even with full power.
- **Handy Management Service**
With the management software, you can remotely monitor and diagnose a repeater. In addition, you can either record or play back the audio freely in digital mode.
- **Innovative LED Design**
The innovative LED and the 2.0 " HD color display would deliver you the repeater status clearly, as well as a pleasing visual experience.
- **Accessory Expansion**
RD98X supports third party to develop accessories expansion via front and rear port of the Repeater. This is achieved via the signal streaming and pin control through the repeater ports.

Main Functions

- **Repeater Diagnostic And Control (RDAC)**
RD98X supports Remote (via IP port to connect to internet) and Local diagnostic (via USB) PC applications to monitor, diagnose and control the repeater status, thus increasing the maintenance efficiency. *Hytera's developed RDAC is able to support multiple master network connection to allow radio administrator to monitor multiple radio network upcoming!
- **Dual Slot Digital Audio Streaming**
RD98X supports streaming of both the voice slots via the rear port accessory pins, allowing third party for capability expansion.
- **Analog Digital Autoswitch**
RD98X supports Analog and Digital channel auto switching, allowing efficient frequency sharing between Analog and Digital users during the digital migration.
- **IP Multi-site Connect**
RD98X supports network interconnect via the IP port of repeater to form a private radio network, allowing wide area coverage to meet dispersed locations data and voice communications.
- **50W High Power**
RD98X supports maximum repeating power of 50W, and thus increasing the system coverage with lesser setup equipments.
- **16 Channels**
RD98X supports maximum of 16 channels, allowing efficient radio network control at different scenarios. The channel change can be performed either via RDAC PC tools, via the repeater's front panels channel knob and via the channel steering from the repeater's rear port.
- **Analog/Digital Operating Mode**
RD98X supports operating mode of Analog and Digital.
- **Analog/Digital Back-to-Back Interconnect**
RD98X supports different operating mode of Analog and Digital to interconnect for voice cross patch, allowing Analog users to communicate to the Digital users and vice versa. This has allowed the smooth migration for Analog users to the digital world!
- **Analog Repeater Knockdown**
RD98X supports repeater knockdown, that when activated via the repeater's rear accessory pin, will disabled the transmit path of the repeater.
- **Multi CTCSS/CDCSS Decode**
RD98X supports decoding up to maximum of 16 CDCSS/CTCSS in Analog channels, allowing repeating of different Analog voice users from various groups.
- **Analog Scan**
RD98X supports Analog voice and signaling scan, allowing repeating of different Analog voice users from various groups.
- **Repeater Access Management**
RD98X supports radio users access control to the repeater, allows better security to prevent un-authorized users from accessing the radio network.
- **Analog/Digital Telephone Interconnect (via DTMF signaling)**
RD98XG supports simplex voice communications between radio and telephone users. It allows a radio user to make a telephone call; or a telephone user to make either a Group or Private call to radio users. This feature utilizes the Commercial Off The Shelf (COTS) Analog Phone Patch boxes and a Plain Old Telephone Service (POTS) line to connect the Repeater to the Corporate Office Phone System (PBX) or Public Switched Telephone Network (PSTN).
- **Continuous Wave Identification (CWID)**
RD98X supports Analog transmission of the repeater identification in Morse code format.

RD98X
Higher Efficiency,
Richer Experience

As a professional repeater built to the DMR standard, RD98X integrates user concerns and actual requirements. Powerful digital feature, remarkable service quality and considerate ergonomic design - It will refresh your communication experience!

Applications

Public Safety
Energy and Forestry

Utility
Business

Transportation
Sports



* indicates functions available in later version.